

FANTECH

Intelligent Ventilation

The stylish **Rapid Response** header box exhaust fan is one of the quietest and most powerful in its class. Its aerodynamic and fully optimised design minimises resistance and produces strong, efficient air flow performance.

One of the quietest & most powerful in its class

At last, an exhaust fan that is sleek looking and does a great job of removing steam and unpleasant odours from bathrooms, ensuites and toilets. The Rapid Response ceiling mounted header box fan features a unique swing clip and removable spigot that makes it very easy to install. Every element of the Rapid Response has been optimised for peak performance and enhanced efficiency.





Low noise





Powerful air flow

Easy to install



Optimised Impeller

Specially designed forward curved centrifugal impeller with an optimised variable radius inlet path. Blades are positioned at specific angles and intervals to achieve maximum air flow and efficiency, resulting in more power and less noise.

Aerodynamic Design

All parts of the fan have been aerodynamically engineered to allow air to flow through the fan with the least possible resistance, resulting in powerful performance matched with smooth and quiet operation. The inlet has been shaped to provide the smoothest entry for air and the expansion chamber is situated in the optimum position to guide air flow out of the fan.

Engineered Grilles

The matching grilles have been aerodynamically engineered to allow air to flow into the fan with minimal possible resistance, resulting in smooth efficient air flow and low noise levels.

Quiet Backdraft Shutter

Our engineering team have developed an ultra quiet backdraft shutter. It produces minimal air flow resistance and requires no power to operate.

Powerful Motor

Dynamically balanced motor with hardened steel shaft and sealed for life silicone ball bearings guarantee an extra long life span matched with high speed operation and performance.

Built To Last

We know this fan has been built correctly with only quality components. This means we can offer a 3 year warranty on our Rapid Response 250 models and a groundbreaking 5 year warranty on our Rapid Response 200 and 250HP models.



Rapid Response 200

Ducted Ceiling Fan

The ultra quiet Rapid Response 200 header box exhaust fan is ideal for odour and dampness removal from toilets, powder rooms, laundries and cupboards. It includes features such as a unique swing clip and removable spigot that makes it very easy to install.

- Advanced impeller and housing design provides powerful air flow with minimal noise.
- Can be retrofitted into an existing standard 8" round fan cut out.
- Low resistance non-return backdraft damper maximises air flow performance.

- Matching grilles are easy to remove, which makes cleaning easy.
- Includes sealed for life ball bearings.
- High strength swing clips make installation easy.
- Available with a modern square or round grille (See page 6). Square grille can be easily rotated to align with walls.
- Available with 3-15 minute adjustable run-on timer (RESPF8-T).
- Comes with spigot to suit both 100mm and 150mm duct.



Rapid Response 250

Ducted Ceiling Fan

The Rapid Response 250 ceiling mounted header box fan features quiet operation and powerful air flow performance. It includes a fully optimised inlet cone and centrifugal impeller that maximises air pressure and ensures rooms are quickly cleared of steam and unpleasant odours. It includes a unique swing clip and removable spigot that makes it very easy to install into a standard 10" round fan cut out.

- Advanced impeller and housing design provides powerful air flow and minimises noise.
- Available with a modern square or round grille.
- Low resistance non-return backdraft damper maximises air flow performance.
- Can be retrofitted into a standard 10" round fan cut out.
- Fitted plug and lead simplifies installation.
- Includes high quality sealed for life ball bearings.



Rapid Response 250HP

Ducted Ceiling Fan

The Rapid Response 250HP header box exhaust fan is one of the quietest and most powerful in its class. Its aerodynamic and fully optimised design minimises air flow resistance and produces powerful, efficient performance.

- Rapid Response 250HP provides strong air flow performance to ensure steam is cleared from rooms such as bathrooms and ensuites.
- It includes features such as a unique swing clip and removable spigot that makes it very easy to install.
- Advanced impeller and housing design provides powerful air flow and minimises noise.
- Can be retrofitted into an existing standard 10" round fan cut out.

- Low resistance non-return backdraft damper maximises air flow performance.
- Matching grilles are easy to remove, which makes cleaning easy.
- Includes high quality sealed for life ball bearings.
- High strength swing clips make installation easy.
- Modern square or round grilles available (See page 6).
 Square grilles can be easily rotated to align with walls.
- Available with 3-15 minute adjustable run-on timer (RESPF150T).

Rapid Response Standard Grilles

The stylish and modern Rapid Response grille is available in round and square designs with white or black finish.

- Innovative design allows grilles to be easily removed for cleaning.
- Available in 2 sizes to suit 8" and 10" Rapid Response header box fan.
- Quick and easy to install to fan body.
- · Can be retrofitted to a previously installed Rapid

See back page for product codes and dimensions





black finish

Rapid Response Grilles with LED Light

The Rapid Response grille with LED light will brighten up any bathroom, ensuite, powder room or toilet. They are quick and easy to install, and feature a stylish, modern design to suit any setting. For added convenience the LED light can be controlled separately to the fan.

- Available in round and square designs with white or black finish.
- Available in 2 sizes to suit 8" and 10" Rapid Response fan.
- · 8" LED model is ideal for toilets and powder rooms, as it includes a light.
- · Can be retrofitted to a previously installed Rapid Response fan.
- · Grilles can be easily removed for cleaning.
- Complies to: AS/NZS 60598.2.2:2001 and AS/NZS 60598.1:2013 Certificate No.: SAA152082.
- Three colour temperature options to match other installed lights.

See back page for product codes, dimensions & specifications.



Round grille white finish with 3 colour temperature LED light



Round grille black finish with 3 colour temperature LED light




Square grille white finish with 3 colour temperature LED light



Square grille black finish with 3 colour temperature LED light

Tri-Switch LED

Grilles come factory pre-set to cool white (4200K), but can be changed to warm white (3000K) or daylight (6000K) by changing the position of Tri-Switch located on back of grille.





Cool White

Warm White Cool White Daylight (Colour Temperature: 3000K) (Colour Temperature: 4200K) (Colour Temperature: 6000K) Colour indicated in drawings above is for illustrative purposes only

Grille to Duct Connector

The easy to install Rapid Response grille to duct connector is designed to fit one of our stylish and modern 8" Rapid Response grilles and flexible duct. The grille to duct connector is suited for ducted systems using an in-line, roof, or external wall mounted fan. Grilles are quick to remove, making them easy to clean.


- · High strength swing clips make installation easy.
- Can be retrofitted into a standard 8" (255mm) round cut out.
- Designed to fit our range of 8" Rapid Response grilles.
- · Suitable for 150mm ducting.


Product Code: RESP8-DCON



Rapid Response Selection Guide

Select suitable fan body size





Installation Made Easy



Long clip-in spigot makes installation and duct connection easier.






Rotate swing clips to hold fan body in place.



Tighten screws so clips clamp onto ceiling board.

Dir	mensional Da	ata															
	Model	Llescription			Dimensi					ons, mm							
Number		Description		Cut Out AØ			В			C 100/150mm spigot		D					
		Fan B	ody														
	RESPF8	8" Ducted ceiling fan		2	55			195		105/170		94/120		0			
녈	RESPF8-T	8" Ducted ceiling fan with run-on tir	ner														
_	RESPF150	10" Ducted ceiling fan		2	90			197		170			120				
	RESPF150T	10" Ducted ceiling fan with run-on tir	ner														
	Model Number	Description	Cut Ou AØ	t B	С	D	Dim	nensi FØ		s, mm ut Out GØ H I			V				
	Trainiso.	Fan Body v			C	D		רש	G	Ø	Н	-	94/1 12 J K	K	L		
	RESPFG10RN	10" Ducted ceiling fan with round grille	290	197	170	120	24	332	_		_	_	_	_	-		
	RESPFG10SQ	10" Ducted ceiling fan with square grille	-	-	-	-	-	_	29	90	197	170	120	30	353		
	Model							Dime	ensio	ions, mm		21 300					
	Number	Description		А			В			С		D					
	Grilles																
	RESPG8-SQWH	8" Square Grille White Finish		300		28			-		-						
	RESPG8-SQWH-TRILED	8" Square Grille White Finish with LED) Light	300			28			-		-					
	RESPG8-SQBK	8" Square Grille Black Finish		300			28			-			-				
	RESPG8-SQBK-TRILED	8" Square Grille Black Finish with LED) Light	300			28			-			-				
	RESPG8-RNWH	8" Round Grille White Finish			-		-			294			19				
0	RESPG8-RNWH-TRILED	8" Round Grille White Finish with LED	Light		-			- 294			19						
	RESPG8-RNBK	8" Round Grille Black Finish			-	-			294		19						
0	RESPG8-RNBK-TRILED	8" Round Grille Black Finish with LED	Light	-			-			294			19				
	RESPG150SQWH	10" Square Grille White Finish	Finish		353		30			-		-					
	RESPG150SQWH-TRILED	10" Square Grille White Finish with LED Light		3	53	30			-			-					
	RESPG150SQBK	10" Square Grille Black Finish		3	53	30			-			-					
	RESPG150SQBK-TRILED	10" Square Grille Black Finish with LED Light		3	353 30			-			-						
	RESPG150RNWH	10" Round Grille White Finish	te Finish		-		-			332			24				
	RESPG150RNWH-TRILED	10" Round Grille White Finish with LED	Light	-			-			332			24				
	RESPG150RNBK	10" Round Grille Black Finish		-		-			-			332			24		
	RESPG150RNBK-TRILED	10" Round Grille Black Finish with LED	Light					332		24							





*RESPF8 comes with spigot to suit both 100mm and 150mm duct.

^{*}RESPF150 comes with spigot to suit 150mm duct only.









Technical Data

Model	Run-on	Air flow [†]		Fan Speed	Average Sound Level	Watts	Volts			
Number	Timer	m³/hr†	L/sec [†]	RPM	dB(A) @ 3m	walls	VOILS			
Fans										
RESPF8	No	216	60	950	29	30	230-240			
RESPF8-T	Yes	210	60	950	29	30	230-240			
RESPF150	No	349	97	950	37	60	230-240			
RESPF150T	Yes	349	97	950	37	00				
RESPFG10RN	No	288	80	950	38	40	230-240			
RESPFG10SQ	No	200	60	930	30	40	230-240			



FANTECH

Intelligent Ventilation

All now without duct and nitings											
Model Number	Description Lumens (LM)		Input Power (W)	Colour Temp (K)	Beam Angle (°)						
Grilles with LED Lights											
RESPG8-SQWH-TRILED	8" Square Grille White Finish with LED Light	1000	12	3000/4200/6000	180						
RESPG8-SQBK-TRILED	8" Square Grille Black Finish with LED Light	1000	12	3000/4200/6000	180						
RESPG8-RNWH-TRILED	8" Round Grille White Finish with LED Light	800	9	3000/4200/6000	180						
RESPG8-RNBK-TRILED	8" Round Grille Black Finish with LED Light	800	9	3000/4200/6000	180						
RESPG150SQWH-TRILED	10" Square Grille White Finish with LED Light	1000	12	3000/4200/6000	180						
RESPG150SQBK-TRILED	10" Square Grille Black Finish with LED Light	1000	12	3000/4200/6000	180						
RESPG150RNWH-TRILED	10" Round Grille White Finish with LED Light	800	9	3000/4200/6000	180						
RESPG150RNBK-TRILED	10" Round Grille Black Finish with LED Light	800	9	3000/4200/6000	180						





Scan the QR Code for more information

Fantech Pty. Ltd.

(+61 3) 9554 7845 Victoria: New South Wales: (02) 8811 0400 South Australia: (08) 8294 0530 Northern Territory: (08) 8947 0447 (07) 3299 9888 Queensland: Western Australia: (08) 9209 4999 A.C.T. (02) 6280 5511 New Zealand: (09) 444 6266



For sales enquiries contact:

Specifications and design subject



FAN0098 04/24 Version 2